

Work/Catch Platforms BOOST®

The BOOST® is a versatile self-propelled pneumatic elevating work platform. The BOOST® lift provides maneuverability, ergonomic positioning and added safety for the operator in hazardous environments where combustible dusts or vapors may be present.

GENERAL INFO


- Hose reel with up to 30 ft. operational travel distance
- Raised platform height: Up to 10'
- Minimum lowered platform height: 2'
- Single Operator Platform Capacity: 300 lbs.
- Platform Length x Width: 2' x 2'
- 43.5" high guard rail
- Pneumatic/Hydraulic power for hazardous areas
- Filter/Regulator/Lubricator
- Quick and easy connection to air source
- Front swivel casters

CONTROLS / CONNECTIONS

- Primary air source connection: 1/2" NPT
- Auxiliary uncoiled air connection in platform: 3/8" NPT
- Lift requires a clean, dry air supply (40 scfm @ 90 psi with a 40°F dew point)
- Fixed hand control with Emergency stop
- Base control to raise and lower platform

TRAVEL SPEEDS

- X-Axis (left/right): 40 fpm
- Z-Axis (up/down): 22 fpm



Model BOOST (Elevating Work Platform)					
Model	Raised Floor Ht.	Lowered Floor Ht.	Max Work Ht.	Overall Length	Overall Width
BOOST	10'	2'	16'	4'-5"	3'-2"
-Slab type machines should only be raised on a hard, flat and level surface -Designed in accordance with applicable ANSI requirements based on machine configuration as originally manufactured for intended applications					



Dimensions shown are nominal. Actual dimensions may vary and are presented with engineering drawings.

Due to continuous product improvement, LPI, Inc. reserves the right to make equipment/specification changes without prior notification.

Work/Catch Platforms BOOST®

APPLICATIONS

The BOOST® single operator lift is designed for use in hazardous or industrial areas where access is needed at elevated heights.

- Paint Booths
- Paint Prep Areas
- Paint Kitchens
- Sanding/Buffering Areas
- Assembly
- Welding
- Maintenance
- Masking/Decal

BOOST Features / Options

1. Hose reel & 1/2" hose for 30 ft. operational travel
2. Hand controls for horizontal & vertical travel
3. Auxiliary uncoiled air supply connection in platform
4. Filter/Regulator/Lubricator with main air shut-off
5. Fork lift pockets for distance transport
6. Auxiliary air regulator*
7. Platform front tool tray*
8. Static discharge ground reel*
9. Base mounted tool tray*
10. Paint pot carrier* (paint pot not included)
11. 360° swivel air connection kit*
12. Wide wheel drive kit for floor grating*
13. Paint gun hook kit*

* Optional



Dimensions shown are nominal. Actual dimensions may vary and are presented with engineering drawings.

Due to continuous product improvement, LPI, Inc. reserves the right to make equipment/specification changes without prior notification.